


**ROBONICDRIVE**

諧波減速機



## 減速機構 Reduction Mechanism

- 通過凸輪使薄壁軸承、柔性齒輪呈橢圓狀變形。
- 柔性齒輪與內齒輪在橢圓形長軸部分發生嚙合。
- 固定內齒輪，使凸輪沿順時針方向旋轉  $360^\circ$  時，柔性齒輪會沿逆時針方向移動內齒輪與柔性齒輪的齒數差部分。



- Flex gear and elastic bearing take elliptic shape with the wave generator inserted.
- Flex gear and internal gear are engaged at both ends of the long axis of the ellipse in a stable manner.
- With the internal gear fixed, when the wave generator is rotated clockwise, the flex gear (output) rotates counterclockwise. And its rotational speed is determined by the tooth count differential between two gears.



## 零件名稱 Parts Name



## 減速比 Ratio



減速比由杯型柔性齒輪和剛性內齒輪來決定  
The reduction ratio is determined by the flex gear and the rigid internal gear.



杯型柔性齒輪齒數 Flex Gear :  $Z_f$   
剛性內齒輪齒數 Internal Gear :  $Z_c$

$$\text{減速比 Ratio} = \frac{-1}{R} = \frac{Z_f - Z_c}{Z_f}$$

$$\text{減速比 Ratio} = \frac{1}{R}$$

※ 輸入旋轉方向與輸出旋轉方向相反。


The input and output rotation directions are opposite.



$$\text{減速比 Ratio} = \frac{1}{R+1}$$

※ 輸入旋轉方向與輸出旋轉方向相同。

The input and output rotation directions are same.



R 為減速機規格表中的減速比。R represents the "Ratio" figure in the specifications table on the catalogue.

# 潤滑劑 Lubricant Information

## 潤滑劑的使用 Lubrication

全合成潤滑油脂  
Synthetic grease No.2.


unit: g

## 潤滑劑的塗抹 Grease Application


DSF 及 DHG 按照右表要求塗抹潤滑劑。  
For DSF and DHG, please apply grease according to the right table.

| 型號<br>Model | DSF / DSG / DHG |     |      |     |
|-------------|-----------------|-----|------|-----|
|             | A               | B   | C    | D   |
| 14          | 1               | 3   | 0.25 | 0.5 |
| 17          | 2               | 6   | 0.5  | 1   |
| 20          | 3               | 9   | 0.75 | 1.5 |
| 25          | 6               | 18  | 1.5  | 3   |
| 32          | 12              | 36  | 3    | 6   |
| 40          | 22              | 66  | 5.5  | 11  |
| 45          | 34              | 102 | 8.5  | 17  |

## 潤滑劑的塗抹部位 Grease Application Location




E 處填充量為空間的 50% 油量。At location E, fill with oil to 50% of the space's capacity.



# 安裝精度 Attachment Fixture Requirement

## DSF-PK




unit: mm

| 型號<br>Model | 14    | 17    | 20    | 25    | 32    | 40    | 45    |
|-------------|-------|-------|-------|-------|-------|-------|-------|
| a           | 0.015 | 0.015 | 0.018 | 0.018 | 0.023 | 0.023 | 0.023 |
| b           | 0.016 | 0.020 | 0.020 | 0.024 | 0.024 | 0.024 | 0.024 |
| c           | 0.010 | 0.012 | 0.014 | 0.016 | 0.020 | 0.020 | 0.020 |
| d           | 0.013 | 0.013 | 0.015 | 0.018 | 0.020 | 0.020 | 0.020 |
| e           | 0.012 | 0.012 | 0.014 | 0.016 | 0.016 | 0.020 | 0.020 |
| f           | 0.016 | 0.020 | 0.024 | 0.024 | 0.024 | 0.024 | 0.024 |

## DSF-AK


## DSG-AK



unit: mm

| 型號<br>Model | 14    | 17    | 20    | 25    | 32    | 40    | 45    |
|-------------|-------|-------|-------|-------|-------|-------|-------|
| a           | 0.020 | 0.020 | 0.020 | 0.025 | 0.025 | 0.025 | 0.025 |
| b           | 0.012 | 0.012 | 0.014 | 0.016 | 0.016 | 0.016 | 0.016 |
| c           | 0.016 | 0.020 | 0.024 | 0.024 | 0.024 | 0.024 | 0.024 |

## DHG-AK



unit: mm

| 型號<br>Model | 14    | 17    | 20    | 25    | 32    | 40    | 45    |
|-------------|-------|-------|-------|-------|-------|-------|-------|
| a           | 0.020 | 0.020 | 0.020 | 0.025 | 0.025 | 0.025 | 0.025 |
| b           | 0.012 | 0.012 | 0.014 | 0.016 | 0.016 | 0.016 | 0.016 |
| c           | 0.016 | 0.020 | 0.024 | 0.024 | 0.024 | 0.024 | 0.024 |

# 傳導力矩 Transmitting Torque

## 螺絲緊固力矩 Tightening Torque for Bolts

unit: Nm

| 螺絲 Bolts                 | M3  | M4  | M5  | M6 | M8 | M10 | M12 |
|--------------------------|-----|-----|-----|----|----|-----|-----|
| 螺絲緊固力矩 Tightening Torque | 1.9 | 4.3 | 8.7 | 15 | 36 | 71  | 128 |

推建議螺絲：強度區分 12.9 以上

Recommended bolt : Strength rating above 12.9

## 傳導力矩 Bolt Specifications and Transmitting Torque

### DSF-AC、DSG-AC、DSF-AK、DSG-AK (組合式 Unit Type)

#### 安裝輸出法蘭 Output flange Attachment


| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32    | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-------|-------|-------|
| 螺絲 Bolt                  |      | M4  | M5  | M6  | M8  | M10   | M10   | M12   |
| 螺絲個數 Bolt Count          |      | 6   | 6   | 8   | 8   | 8     | 8     | 8     |
| 安裝 PCD Bolt PCD          | mm   | 23  | 27  | 32  | 42  | 55    | 68    | 82    |
| 緊固力矩 Tightening Torque   | Nm   | 4.3 | 8.7 | 15  | 36  | 71    | 71    | 128   |
| 傳導力矩 Transmitting Torque | Nm   | 56  | 106 | 238 | 566 | 1,177 | 1,500 | 2,600 |

#### 安裝內齒輪 Internal Gear Attachment (DSF)

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32    | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-------|-------|-------|
| 螺絲 Bolt                  |      | M4  | M4  | M5  | M5  | M6    | M8    | M8    |
| 螺絲個數 Bolt Count          |      | 6   | 6   | 6   | 8   | 12    | 8     | 12    |
| 安裝 PCD Bolt PCD          | mm   | 65  | 71  | 82  | 96  | 125   | 144   | 164   |
| 緊固力矩 Tightening Torque   | Nm   | 4.3 | 4.3 | 8.7 | 8.7 | 15    | 36    | 36    |
| 傳導力矩 Transmitting Torque | Nm   | 140 | 148 | 276 | 435 | 1,213 | 1,695 | 2,840 |

#### 安裝內齒輪 Internal Gear Attachment (DSG)

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32    | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-------|-------|-------|
| 螺絲 Bolt                  |      | M4  | M4  | M5  | M5  | M6    | M8    | M8    |
| 螺絲個數 Bolt Count          |      | 8   | 8   | 8   | 10  | 12    | 10    | 12    |
| 安裝 PCD Bolt PCD          | mm   | 65  | 71  | 82  | 96  | 125   | 144   | 164   |
| 緊固力矩 Tightening Torque   | Nm   | 4.3 | 4.3 | 8.7 | 8.7 | 15    | 36    | 36    |
| 傳導力矩 Transmitting Torque | Nm   | 180 | 194 | 361 | 532 | 1,213 | 2,080 | 2,840 |



## 傳導力矩 Bolt Specifications and Transmitting Torque

### DSF-PC、DSF-PK (組件式 Component Type)

#### 安裝杯型柔性齒輪 Cup-Type Flex Gear Attachment


| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32  | 40  | 45    |
|--------------------------|------|-----|-----|-----|-----|-----|-----|-------|
| 螺絲 Bolt                  |      | M4  | M5  | M5  | M6  | M8  | M10 | M12   |
| 螺絲個數 Bolt Count          |      | 6   | 6   | 8   | 8   | 8   | 8   | 8     |
| 安裝 PCD Bolt PCD          | mm   | 17  | 19  | 24  | 30  | 40  | 50  | 54    |
| 緊固力矩 Tightening Torque   | Nm   | 4.3 | 8.7 | 8.7 | 15  | 36  | 71  | 128   |
| 傳導力矩 Transmitting Torque | Nm   | 41  | 75  | 126 | 223 | 539 | 910 | 1,440 |

#### 安裝內齒輪 Internal Gear Attachment (DSF)

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32  | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-----|-------|-------|
| 螺絲 Bolt                  |      | M3  | M3  | M3  | M4  | M5  | M6    | M8    |
| 螺絲個數 Bolt Count          |      | 6   | 12  | 12  | 12  | 12  | 12    | 12    |
| 安裝 PCD Bolt PCD          | mm   | 44  | 54  | 62  | 75  | 100 | 120   | 140   |
| 緊固力矩 Tightening Torque   | Nm   | 1.9 | 1.9 | 1.9 | 4.3 | 8.7 | 15    | 15    |
| 傳導力矩 Transmitting Torque | Nm   | 53  | 128 | 147 | 313 | 666 | 1,146 | 2,430 |


#### 安裝內齒輪 Internal Gear Attachment (DSG)

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32  | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-----|-------|-------|
| 螺絲 Bolt                  |      | M3  | M3  | M3  | M4  | M5  | M6    | M8    |
| 螺絲個數 Bolt Count          |      | 8   | 16  | 16  | 16  | 16  | 16    | 16    |
| 安裝 PCD Bolt PCD          | mm   | 44  | 54  | 62  | 75  | 100 | 120   | 140   |
| 緊固力矩 Tightening Torque   | Nm   | 1.9 | 1.9 | 1.9 | 4.3 | 8.7 | 15    | 15    |
| 傳導力矩 Transmitting Torque | Nm   | 71  | 167 | 196 | 401 | 892 | 1,508 | 3,234 |



#### 銷子孔的追加 Reinforcement

柔性齒輪安裝的傳導力矩未滿足要求時，同時使用銷子。銷子孔可根據需求追加。  
Pins can be added if the transmittable torque at the flex gear interface is not sufficient. As an option, holes can be added.



## 傳導力矩 Bolt Specifications and Transmitting Torque




### DHG

#### 安裝帽型柔性齒輪 Hat-Type Flex Gear Attachment

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32    | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-------|-------|-------|
| 螺絲 Bolt                  |      | M3  | M3  | M3  | M4  | M5    | M6    | M6    |
| 螺絲個數 Bolt Count          |      | 8   | 12  | 12  | 12  | 12    | 12    | 18    |
| 安裝 PCD Bolt PCD          | mm   | 64  | 74  | 84  | 102 | 132   | 158   | 180   |
| 緊固力矩 Tightening Torque   | Nm   | 1.9 | 1.9 | 1.9 | 4.3 | 8.7   | 15    | 15    |
| 傳導力矩 Transmitting Torque | Nm   | 119 | 206 | 234 | 495 | 1,037 | 1,392 | 2,088 |

#### 安裝內齒輪 Internal Gear Attachment

| 型號 Model                 | Unit | 14  | 17  | 20  | 25  | 32  | 40    | 45    |
|--------------------------|------|-----|-----|-----|-----|-----|-------|-------|
| 螺絲 Bolt                  |      | M3  | M3  | M3  | M4  | M5  | M6    | M8    |
| 螺絲個數 Bolt Count          |      | 8   | 16  | 16  | 16  | 16  | 16    | 12    |
| 安裝 PCD Bolt PCD          | mm   | 44  | 54  | 62  | 77  | 100 | 122   | 140   |
| 緊固力矩 Tightening Torque   | Nm   | 1.9 | 1.9 | 1.9 | 4.3 | 8.7 | 15    | 36    |
| 傳導力矩 Transmitting Torque | Nm   | 71  | 167 | 196 | 419 | 892 | 1,528 | 3,234 |



# 輸入部位構造 Input Section Structure


## 輸入部位構造 Input Section Structure

輸入部位構造分為鍵槽型與迫緊型，因輸入孔徑等差異而不同。

There are two types of input section structure, keyway and collet + keyway.


鍵槽型

Keyway Type




迫緊型

Collet + Keyway



## 入力孔徑尺寸 Input Hole Diameter



## 入力鍵槽尺寸 Input Bore Dimension


unit: mm

| 型號 Model          | 14    | 17   | 20       | 25        | 32        | 40        | 45        |
|-------------------|-------|------|----------|-----------|-----------|-----------|-----------|
| 入力孔徑 Input Bore B | 6、8   | 8    | 8、14     | 11、14     | 14、19     | 19、24     | 19、24     |
| 鍵槽寬 W             | 2、3   | 3    | 3、5      | 4、5       | 5、6       | 6、8       | 6、8       |
| 鍵高 H              | 7、9.4 | 9.4  | 9.4、16.3 | 12.7、16.3 | 16.3、21.8 | 21.8、27.3 | 21.8、27.3 |
| 螺絲                | 2-M4  | 2-M4 | 4-M4     | 4-M5      | 4-M5      | 4-M5、4-M6 | 4-M6      |
| 安裝 PCD            | 18    | 22   | 25       | 32        | 36        | 50        | 50        |
| A                 | 14    | 16   | 21       | 24        | 30        | 36        | 36        |
| C                 | 2.3   | 4.2  | 4.3      | 6         | 5         | 7         | 5         |
| D                 | 10    | 12.5 | 13.5     | 14.5      | 16        | 20        | 20        |

# 馬達安裝方法 Motor Mounting Instructions


## 安裝方式 Installation Method 1

- 步驟 1：將法蘭安裝至馬達上  
 步驟 2：將諧波產生器安裝至馬達軸上  
 步驟 3：安裝至組合型產品元件  
 step 1: Attach the flange on to the motor.  
 step 2: Attach the wave generator on to the motor shaft.  
 step 3: Attach the unit.



## 安裝方式 Installation Method 2

- 步驟 1：將諧波產生器安裝至馬達軸上  
 步驟 2：將法蘭安裝至馬達上  
 步驟 3：安裝至組合型產品元件  
 step 1: Attach the wave generator on to the motor shaft.  
 step 2: Attach the flange on to the motor.  
 step 3: Attach the unit.




### 安裝操作時的注意事項 Caution during installation

- 組裝各零部件時，不可過度用力頂壓。
- 注意不可傾斜插入諧波產生器。
- Do not use excessive force while mating parts.
- Please watch for tilting during input section assembly wave generator.

# 注意事項 Installation and Assembly Instructions

## 入力軸 / 出力軸の支撐 (DSF / DSG) Shaft Installation Instruction

入力軸 / 出力軸請採用承受作用於軸部的徑向負荷 / 軸向負荷的支撐構造。(下圖為參考實例)  
Please design the support structure for input shaft and output shaft so that both radial and axial loads are supported. (Diagram below shows an example)




## 安裝方法 (DSF / DSG) Attachment Flang Requirement

安裝與杯型柔性齒輪相連接的法蘭時，為了防止造成杯型柔性齒輪破損，請保證下表所示尺寸。

For the attachment flange that comes in contact with cup-type flex gear, please build the corner radius according to the table below, in order to prevent damage.

unit: mm

| 型號 Model | 14  | 17  | 20  | 25  | 32  | 40  | 45  |
|----------|-----|-----|-----|-----|-----|-----|-----|
| R        | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 |
| D        | 23  | 26  | 31  | 38  | 50  | 65  | 73  |



## 電機安裝用法蘭尺寸 (DSF / DSG)

### Size Requirement of the Flange for Motor Attachment


將電機安裝至組合型元件產品時，需要安裝專用法蘭。

電機安裝專用法蘭尺寸請按照下表所示要求執行。

An attachment flange is required in order to attach a unit type to the motor. The table below shows the dimension requirement for the flange.

unit: mm

| 型號 Model | 14   | 17   | 20   | 25   | 32   | 40    | 45    |
|----------|------|------|------|------|------|-------|-------|
| B        | 56   | 63   | 72   | 86   | 113  | 127   | 148   |
| T        | 38H7 | 48H7 | 56H7 | 67H7 | 90H7 | 110H7 | 124H7 |
| t        | 3    | 3    | 3.5  | 4    | 4    | 5     | 5     |
| a        | 0.03 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04  | 0.04  |
| b        | 0.03 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04  | 0.04  |



# 壽命 Service Life

## 波產生器的壽命 Service Life of the Wave Generator

減速機的使用壽命，由波產生器軸承的壽命決定。和一般滾珠軸承相同，由轉速與負載轉矩計算求出。  
The service life of reducer is determined by the service of the wave generator bearing, and you can calculate this by the rotational speed and the load torque just as with a general ball bearing.

### 壽命時間 Service Life

| 機型 Type                                | DSF、DSG、DHG  |
|----------------------------------------|--------------|
| $L_{10}$ (10% 受損機率 Damage Probability) | 7,000 horus  |
| $L_{50}$ (平均壽命 Average Service Life)   | 35,000 horus |

※ 額定表記載之額定轉速、額定轉矩下的運轉壽命。

Service is based on the rated rotational speed and rated torque from the ratings.

依據實際運轉條件的壽命時間 ( $L_h$ ) 公式

Calculation formula for service Life ( $L_h$ ) by actual operation condition

$$L_h = L_n \cdot \left( \frac{Tr}{Tav} \right)^3 \left( \frac{Nr}{Nav} \right)$$


$L_n$ :  $L_{10}$  或  $L_{50}$  時的壽命時間 Service Life of  $L_{10}$  or  $L_{50}$

$Tr$ : 額定轉矩 Rated Torque

$Nr$ : 額定轉速 Rated Rotational Speed

$Tav$ : 輸出端的平均負載轉矩 Average Load Torque on the Output Side

$Nav$ : 平均輸入轉速 Average Input Rotational Speed



請維持在「一般時運轉使用區域」中使用。若超出「一般時運轉使用區域」使用範圍，將加速減速機的損壞。  
上述圖表未考慮齒面磨耗等潤滑壽命，請以上述圖表作為參考值。

Use it within the range of "Normal operation area". Using it beyond "Emergency operation area" may result in damaging reducer earlier than usual.

Lubricant life such as for abrasion on the tooth surface is not taken into consideration in the graph described above. Use the graph above as reference values.

# 強度 Intensity

## 柔性齒輪的強度 Intensity of Flex Gear

柔性齒輪會反覆發生彈性變形，所以減速機的傳動轉矩以柔性齒輪的齒根疲勞強度為基準。  
額定轉矩、起動與停止時的容許峰值轉矩等數值，為柔性齒輪的齒根疲勞極限之內的數值。  
若施加超過起動或停止峰值轉矩的衝擊轉矩，恐將產生疲勞破壞。  
為了避免產生疲勞破壞，設有衝擊轉矩的施加次數限制。但衝擊轉矩的最大值不得超過瞬間容許最大轉矩。

As flexs gear repeats elastic deformation, the transmission torque of reducer is calculated based on the fatigue strength of the bottom of the flex gear.

Values of the rated torque and permissible peak torque for start and stop are those within the fatigue limit of the bottom of the flexs gear.

If impact torque that exceeds the peak torque for start and stop is applied, it could generate fatigue fracture.

Therefore, the number of applications of impact torque is limited to prevent possible fatigue fracture.

However, the maximum value of the impact torque cannot exceed the permissible maximum momentary torque.

在波產生器承受衝擊轉矩時，柔性齒輪的彈性變形次數限制：

Restriction on the bending frequency of the flexs gear by the rotation of the wave generator while the impact torque is applied:

$1.0 \times 10^4$  (次 frequency)

基於此一彈性變形次數限制，可求出衝擊轉矩施加的容許次數。

You can calculate the permissible frequency of impact torques from this restriction on the bending frequency.

### 計算公式 Calculation Formula

$$N = \frac{1.0 \times 10^4}{2 \times \frac{n}{60} \times t}$$

|           |                                        |           |
|-----------|----------------------------------------|-----------|
| 容許次數      | Permissible Frequency                  | : N 次     |
| 衝擊轉矩的施加時間 | Time that Impact Torque is Applied     | : t sec   |
| 當時的波產生器轉速 | Rotational Speed of the Wave Generator | : n r/min |

波產生器旋轉 1 圈，將使柔性齒輪產生 2 次彈性變形。

The flexs gear bends two times by one cycle of the wave generator.

## 屈曲轉矩 Buckling Torque

波產生器為固定狀態下，對柔性齒輪（輸出）施加過度轉矩時，將引起柔性齒輪的塑性變形，並將導致柔性齒輪中部發生屈曲，進而破壞。此時的轉矩，稱為屈曲轉矩。


When excess torque is applied to the flexs gear (output) with the wave generator fixed, the flexs gear causes elastic deformation, buckles on the body before long and will be destroyed. The torque at the time is called buckling torque.

## 棘輪轉矩 Ratcheting Torque

運轉中若施加過度的衝擊轉矩，可能出現柔性齒輪未破損，但剛性齒輪與柔性齒輪的嚙合瞬間脫開的情況。此一現象稱為棘輪效應，此時的轉矩稱為棘輪轉矩。

When excess impact torque is applied during operation, the engagement of the teeth between the internal gear and the flexs gear may be put momentarily out of alignment instead of damaging the flexs gear. This phenomenon is called ratcheting, and the torque is called "ratcheting torque".

齒輪嚙合偏向單側的情況 When the engagement of the teeth is out of alignment



- ※ 發生棘輪效應時，無法正常嚙合，可能如圖般偏往單側。如在此狀態下運轉，將因產生振動引起彈性齒杯破損。
- ※ 一旦發生棘輪效應，齒尖將會磨耗，第二次以後的棘輪效應發生轉矩值將會降低。
- ※ When ratcheting is caused, the teeth may not be correctly engaged and become out of alignment as shown. As operating the drive in this condition will generate vibration and damage the flexspline, adequate care should be exercised.
- ※ Once ratcheting is caused, the tips of the teeth are worn and the torque value generated by ratcheting will be lowered. Pay due attention to this point as well.


此一情況，稱為空轉。 This condition is called "dedoi-dal".

## 剛性 Stiffness

固定輸入側，將力矩施加至輸出側時的彈簧常數與扭曲角度。

In this context, stiffness is the output shaft twisting angle and the spring coefficient, while torque load is applied to the output shaft with input side fixed.

- $K_1$ ..... 力矩  $0 \sim T_1$  的彈簧常數  
Spring coefficient at  $0 \sim T_1$  torque
- $K_2$ ..... 力矩  $T_1 \sim T_2$  的彈簧常數  
Spring coefficient at  $T_1 \sim T_2$  torque
- $K_3$ ..... 力矩  $T_2 \sim$  的彈簧常數  
Spring coefficient at  $T_2 \sim$  torque



| 減速比 Ratio        | 代號 Code    | 單位 Unit         | 14   | 17   | 20   | 25   | 32   | 40    | 45    |
|------------------|------------|-----------------|------|------|------|------|------|-------|-------|
| -                | $T_1$      | Nm              | 2    | 4    | 8    | 16   | 30   | 62    | 76    |
| -                | $T_2$      | Nm              | 6.8  | 12   | 24   | 50   | 110  | 210   | 280   |
| 50               | $K_1$      | X $10^4$ Nm/rad | 0.28 | 0.70 | 1.20 | 2.80 | 5.60 | 11.00 | 15.00 |
|                  | $K_2$      | X $10^4$ Nm/rad | 0.45 | 0.86 | 1.80 | 3.40 | 7.20 | 14.00 | 20.00 |
|                  | $K_3$      | X $10^4$ Nm/rad | 0.60 | 1.70 | 2.60 | 4.20 | 8.50 | 18.00 | 24.00 |
|                  | $\theta_1$ | arcmin          | 2.45 | 1.96 | 2.29 | 1.72 | 1.84 | 1.93  | 1.74  |
|                  | $\theta_2$ | arcmin          | 5.19 | 4.79 | 4.58 | 5.05 | 5.25 | 4.51  | 4.80  |
| 80<br>100<br>120 | $K_1$      | X $10^4$ Nm/rad | 0.46 | 0.92 | 1.50 | 3.40 | 7.00 | 12.00 | 17.00 |
|                  | $K_2$      | X $10^4$ Nm/rad | 0.65 | 1.20 | 1.80 | 3.80 | 8.20 | 18.00 | 23.00 |
|                  | $K_3$      | X $10^4$ Nm/rad | 0.70 | 1.80 | 2.60 | 4.60 | 9.70 | 22.00 | 29.00 |
|                  | $\theta_1$ | arcmin          | 1.50 | 1.50 | 1.80 | 1.62 | 1.47 | 1.78  | 1.54  |
|                  | $\theta_2$ | arcmin          | 3.59 | 3.43 | 4.58 | 4.52 | 4.60 | 4.00  | 4.18  |





※ 表中數值為平均值。 Average value shown in the table.

# 入力軸容許負荷 Maximum Load at Input Shaft

## 軸承規格 Bearing Specification


unit: N

| 系列<br>Series | 型號<br>Model | 軸承 A Bearing A                       |                                     | 軸承 B Bearing B                       |                                     | a    | b    |
|--------------|-------------|--------------------------------------|-------------------------------------|--------------------------------------|-------------------------------------|------|------|
|              |             | 基本動態額負荷<br>Basic Dynamic Load Rating | 基本靜態額負荷<br>Basic Static Load Rating | 基本動態額負荷<br>Basic Dynamic Load Rating | 基本靜態額負荷<br>Basic Static Load Rating |      |      |
|              |             | Co                                   | Cor                                 | Co                                   | Cor                                 |      |      |
|              |             | N                                    | N                                   | N                                    | N                                   |      |      |
| DHG-O        | 14          | 5,000                                | 2,450                               | 5,000                                | 2,450                               | 16   | 27.5 |
|              | 17          | 5,400                                | 2,950                               | 5,400                                | 2,950                               | 16.0 | 31.0 |
|              | 20          | 5,650                                | 3,400                               | 5,650                                | 3,400                               | 14.5 | 27.5 |
|              | 25          | 6,150                                | 4,200                               | 6,150                                | 4,200                               | 15.5 | 31   |
|              | 32          | 17,700                               | 10,900                              | 8,200                                | 6,100                               | 20.0 | 36.0 |
|              | 40          | 25,200                               | 17,300                              | 14,300                               | 10,600                              | 24.5 | 43.5 |
|              | 45          | 21,700                               | 16,100                              | 14,900                               | 11,500                              | 24.5 | 46.5 |
| DHG-S        | 14          | 5,700                                | 1,950                               | 2,800                                | 910                                 | 23   | 23   |
|              | 17          | 6,400                                | 2,400                               | 2,800                                | 910                                 | 25.0 | 25.5 |
|              | 20          | 7,000                                | 2,850                               | 2,800                                | 910                                 | 30.5 | 27.5 |
|              | 25          | 7,500                                | 3,250                               | 5,400                                | 2,250                               | 36.0 | 30.5 |
|              | 32          | 11,700                               | 5,050                               | 7,000                                | 2,850                               | 39.0 | 37.0 |
|              | 40          | 17,500                               | 7,850                               | 11,700                               | 5,050                               | 46.5 | 45.0 |
|              | 45          | 17,500                               | 7,850                               | 12,600                               | 5,850                               | 46.5 | 50.5 |



# 薄壁軸承壽命計算 Life Span for the Elastic Bearing

## 運轉類型 Operation Cycle Example



### (1) 平均輸出力矩 / 最大輸出力矩的計算 Calculation Formula for Output Torque

|                                    |     |    |                                                                                                                                                                                 |
|------------------------------------|-----|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 平均輸出力矩<br>Average Output Torque    | Tao | Nm | $Tao = \sqrt[3]{\frac{n_1 \cdot t_1 \cdot  T_1 ^3 + n_2 \cdot t_2 \cdot  T_2 ^3 + \dots + n_n \cdot t_n \cdot  T_n ^3}{n_1 \cdot t_1 + n_2 \cdot t_2 + \dots + n_n \cdot t_n}}$ |
| 最大輸出力矩<br>Peak Output Torque Value | Tmo | Nm | $Tmo = T_1, T_2, \dots, T_n$ 的最大值 Largest Among                                                                                                                                 |

※ 請確認最大輸出力矩為容許最大輸出值以下。

Please make sure the peak output torque is below the maximum output torque in the specification table.

### (2) 平均輸入轉速 / 最高輸入轉速的計算 Calculation Formula for Input Speed

|                                         |     |       |                                                                                               |
|-----------------------------------------|-----|-------|-----------------------------------------------------------------------------------------------|
| 平均輸出轉速<br>Average Output Rotation Speed | nao | r/min | $nao = \frac{n_1 \cdot t_1 + n_2 \cdot t_2 + \dots + n_n \cdot t_n}{t_1 + t_2 + \dots + t_n}$ |
| 最高輸出轉速<br>Peak Output Rotation Speed    | nmo | r/min | $nmo = n_1, n_2, \dots, n_n$ 的最大值 Largest Among                                               |
| 平均輸入轉速<br>Average Input Speed           | nai | r/min | $nai = nao \cdot R$ (R = 減速比 Ratio)                                                           |
| 最高輸入轉速<br>Peak Input speed Value        | nmi | r/min | $nmi = nmo \cdot R$ (R = 減速比 Ratio)                                                           |

※ 請確認最高輸入轉速為容許最高輸入轉速值以下。

Please make sure the peak input speed value is below the maximum input speed in the specification table.

### (3) 壽命時間的計算 Calculation Formula for Life Span

|                                                    |     |       |                                                                                      |
|----------------------------------------------------|-----|-------|--------------------------------------------------------------------------------------|
| 薄壁軸承壽命時間<br>Part Life Span for the Elastic Bearing | Lhe | h     | $Lhe = 7000 \cdot \left(\frac{Tar}{Tao}\right)^3 \cdot \left(\frac{nar}{nai}\right)$ |
| 額定力矩<br>Rating Torque                              | Tar | Nm    | 性能表中所記容許平均力矩<br>Nominal Output Torque in the Specification Table                     |
| 額定輸入轉速<br>Rating Input Rotation Speed              | nai | r/min | 2000 r/min                                                                           |

# 主軸承 Main Bearing


主軸承規格 ( 交叉圓柱滾子軸承 )

## Main Bearing Specification (Crossed Roller Bearing)


| 機型<br>Type       | 型號<br>Model | 滾軸節圓直徑<br>Pitch Circle Diameter<br>of the Bearing Rollers | 偏移量<br>Offset | 基本動態額定負荷<br>Basic Dynamic<br>Load Rating | 基本靜態額定負荷<br>Basic Static<br>Load Rating | 容許力矩荷重<br>Allowable<br>Moment | 力矩剛性<br>Moment<br>Rigidity |
|------------------|-------------|-----------------------------------------------------------|---------------|------------------------------------------|-----------------------------------------|-------------------------------|----------------------------|
|                  |             | Dm                                                        | L             | Cr                                       | Cor                                     | Mc                            | Km                         |
|                  |             | mm                                                        | mm            | N                                        | N                                       | kgfm                          | kgfm/arcmin                |
| DSF<br>DSG       | 14          | 36.5                                                      | 9.5           | 4,800                                    | 7,200                                   | 4.2                           | 1.3                        |
|                  | 17          | 42.5                                                      | 9.5           | 5,500                                    | 8,250                                   | 6.5                           | 2.3                        |
|                  | 20          | 48.9                                                      | 8.8           | 7,050                                    | 10,580                                  | 9.3                           | 3.8                        |
|                  | 25          | 61                                                        | 10.8          | 9,900                                    | 14,800                                  | 16                            | 7.2                        |
|                  | 32          | 84.8                                                      | 13.0          | 12,900                                   | 19,300                                  | 32                            | 16                         |
|                  | 40          | 92.5                                                      | 14.5          | 16,800                                   | 25,200                                  | 46                            | 27                         |
|                  | 45          | 112.8                                                     | 14.5          | 22,000                                   | 33,000                                  | 70                            | 42                         |
| DHG-AC<br>DHG-AK | 14          | 53.8                                                      | 10.3          | 6,000                                    | 8,800                                   | 7.6                           | 2.5                        |
|                  | 17          | 61.5                                                      | 11.9          | 10,700                                   | 16,800                                  | 12.6                          | 4.6                        |
|                  | 20          | 70.4                                                      | 12.0          | 15,000                                   | 22,700                                  | 19.1                          | 7.5                        |
|                  | 25          | 84.5                                                      | 14.1          | 22,400                                   | 37,000                                  | 26.3                          | 11.6                       |
|                  | 32          | 108.0                                                     | 15.9          | 39,400                                   | 65,100                                  | 59.1                          | 29.6                       |
|                  | 40          | 135.0                                                     | 19.0          | 44,600                                   | 74,000                                  | 86.6                          | 53.2                       |
|                  | 45          | 154.0                                                     | 20.5          | 65,400                                   | 98,000                                  | 115                           | 76.3                       |
| DHG-O<br>DHG-S   | 14          | 53.8                                                      | 21.8          | 6,000                                    | 8,800                                   | 7.6                           | 2.5                        |
|                  | 17          | 61.5                                                      | 23.9          | 10,700                                   | 16,800                                  | 12.6                          | 4.6                        |
|                  | 20          | 70.4                                                      | 25.5          | 15,000                                   | 22,700                                  | 19.1                          | 7.5                        |
|                  | 25          | 84.5                                                      | 29.6          | 22,400                                   | 37,000                                  | 26.3                          | 11.6                       |
|                  | 32          | 108.0                                                     | 36.4          | 39,400                                   | 65,100                                  | 59.1                          | 29.6                       |
|                  | 40          | 135.0                                                     | 44.5          | 44,600                                   | 74,000                                  | 86.6                          | 53.2                       |
|                  | 45          | 154.0                                                     | 47.5          | 65,400                                   | 98,000                                  | 115                           | 76.3                       |

## 主軸承壽命計算 Part Life Span for the Main Bearing

運轉類型 Operation Cycle Example



外部負荷 External Load



### (1) 最大負荷慣量的計算 Calculation Formula for the Largest Working Moment

|                               |     |    |                                                    |
|-------------------------------|-----|----|----------------------------------------------------|
| 最大負荷慣量<br>Peak Working Moment | Mm  | Nm | $Mm = Frm \cdot (Lr + L) + Fam \cdot La$           |
| 最大徑向負荷<br>Peak Radial Load    | Frm | N  | $Frm = Fr_1, Fr_2, \dots, Fr_n$ 的最大值 Largest Among |
| 最大軸向負荷<br>Peak Axial Load     | Fam | N  | $Fam = Fa_1, Fa_2, \dots, Fa_n$ 的最大值 Largest Among |

※ 請確認最大負荷慣量為容許慣量值以下。

Please make sure the peak working moment is below the maximum allowable moment.

### (2) 平均徑向負荷 / 軸向負荷 / 平均輸出轉速 / 平均負荷慣量的計算

Calculation Formula for Average Radial Load, Axial Load, Average Output Rotation Speed, Average Working Moment.

|                                         |     |       |                                                                                                                                                                                                                            |
|-----------------------------------------|-----|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 平均徑向負荷<br>Average Radial Load           | Fra | N     | $Fra = \frac{\sqrt[10]{n_1 \cdot t_1 \cdot  Fr_1 ^{\frac{10}{3}} + n_2 \cdot t_2 \cdot  Fr_2 ^{\frac{10}{3}} + \dots + n_n \cdot t_n \cdot  Fr_n ^{\frac{10}{3}}}}{n_1 \cdot t_1 + n_2 \cdot t_2 + \dots + n_n \cdot t_n}$ |
| 平均軸向負荷<br>Average Axial Load            | Faa | N     | $Faa = \frac{\sqrt[10]{n_1 \cdot t_1 \cdot  Fa_1 ^{\frac{10}{3}} + n_2 \cdot t_2 \cdot  Fa_2 ^{\frac{10}{3}} + \dots + n_n \cdot t_n \cdot  Fa_n ^{\frac{10}{3}}}}{n_1 \cdot t_1 + n_2 \cdot t_2 + \dots + n_n \cdot t_n}$ |
| 平均輸出轉速<br>Average Output Rotation Speed | nao | r/min | $nao = \frac{n_1 \cdot t_1 + n_2 \cdot t_2 + \dots + n_n \cdot t_n}{t_1 + t_2 + \dots + t_n}$                                                                                                                              |
| 平均負荷慣量<br>Average Working Moment        | Ma  | Nm    | $Ma = Fra \cdot (Lr + L) + Faa \cdot La$                                                                                                                                                                                   |

### (3) 負荷系數 / 動態等價徑向負荷的計算

Calculation Formula for the Loading Factor, Equivalent Radial Load

|                                    |        |   |                                                                |
|------------------------------------|--------|---|----------------------------------------------------------------|
| 負荷系數<br>Average Working Moment     | Xc, Yc | - | $\frac{Faa}{Fra + 2Ma / Dm} \leq 1.5$ 時, $Xc = 1.0, Yc = 0.45$ |
|                                    |        | - | $\frac{Faa}{Fra + 2Ma / Dm} > 1.5$ 時, $Xc = 0.67, Yc = 0.67$   |
| 動態等價徑向負荷<br>Equivalent Radial Load | Pc     | N | $Pc = Xc \cdot (Fra + 2Ma / Dm) + Yc \cdot Faa$                |

### (4) 主軸承壽命時間的計算 Life Span for the Main Bearing

|                                           |     |   |                                                                                             |
|-------------------------------------------|-----|---|---------------------------------------------------------------------------------------------|
| 主軸承壽命時間<br>Life Span for the Main Bearing | Lhc | h | $Lhc = \frac{10^6}{60 \cdot nao} \cdot \left( \frac{C}{fw \cdot Pc} \right)^{\frac{10}{3}}$ |
| 衝擊系數<br>Impact Factor                     | fw  | - | 1.0 : 未伴隨衝擊時 No Shock                                                                       |
|                                           |     | - | 1.2 : 伴隨些許衝擊時 With Some Shock                                                               |
|                                           |     | - | 1.5 : 伴隨振動衝擊時 With Shock and Vibration                                                      |

# 特性數據 Characteristics Data

unit: arc min


## 角度傳達精度

### Transmission Angular Accuracy

在無負荷條件下使入力軸旋轉時，理論上輸出旋轉角度與實際輸出旋轉角度的差值。

It is the difference between the measured output rotation angle and the theoretical angle, while input shaft is rotated with no load.

| 機型<br>Type | 減速比<br>Ratio | 14  | 17  | 20  | 25  | 32  | 40  | 45  |
|------------|--------------|-----|-----|-----|-----|-----|-----|-----|
| DSF<br>DSG | 50           | 2.0 | 2.0 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 80           | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 100          | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 120          | -   | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| DHG        | 50           | 2.0 | 2.0 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 80           | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 100          | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 120          | -   | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |



## 震動 On Vibration

ROBONICDRIVE 帶有的角傳動誤差成分，有時會顯現為負載端的慣性旋轉振動。

尤其是包含 ROBONICDRIVE 的振動系固有振動數與機體或負載慣性固有振動數重疊時，將形成共振狀態，ROBONICDRIVE 的角傳動誤差成分將會增幅，因此請嚴格遵守各系列的設計指南。

另外，ROBONICDRIVE 的角傳動誤差成分主要來源，是由於 ROBONICDRIVE 結構上輸入軸旋轉 1 次會出現 2 次誤差成分。因此，誤差主要成分的頻率是輸入頻率的 2 倍。

The angle transmission error elements of ROBONICDRIVE may appear as rotating vibration of the load side inertia.

Especially, when the characteristic frequency of the vibration system including ROBONICDRIVE overlaps that of the chassis or load inertia, it generates a resonant condition that amplifies angle transmission error elements of ROBONICDRIVE. Observe the design guide of each series.

Two angle transmission error elements of ROBONICDRIVE correspond to a cycle of the input shaft from the mechanical viewpoint of ROBONICDRIVE. Therefore, the frequency is double the input frequency as it is the main element of the error.

$f$  ..... 包含 ROBONICDRIVE 的振動系固有振動數 [Hz]

The characteristic frequency of the vibration system including ROBONICDRIVE

$$f = \frac{1}{2\pi} \sqrt{\frac{K}{J}}$$

$K$  ..... ROBONICDRIVE 的彈簧常數 [Nm/rad]

Spring constant of ROBONICDRIVE

$J$  ..... 負載慣性 [kgm<sup>2</sup>]

Load inertia

假設包含 ROBONICDRIVE 的振動系固有振動數為  $f=15\text{Hz}$ ，此時的輸入轉速 (N) 為

If the characteristic frequency of the vibration system including ROBONICDRIVE is  $F=15\text{Hz}$ , the input rotation speed (N) is expressed as shown below.

$$N = \frac{15}{2} \cdot 60 = 450 \text{ r/min}$$

・且於該轉速帶 (450 r/min) 發生共振。

The resonant condition is generated in the rotating speed area (450 r/min).

## 滯後損失 Hysteresis Loss


輸入側固定後，將力矩施加至輸出側且 0 力矩時的扭曲角度差。

When torque load is applied at the output shaft in alternate direction repeatedly with input shaft fixed, there is residual twisting angle when torque is back to zero.

In this context, hysteresis loss is the difference in the forward and backward twisting angle.

unit: arcmin

| 機型<br>Type | 減速比<br>Ratio | 14  | 17  | 20  | 25  | 32  | 40  | 45  |
|------------|--------------|-----|-----|-----|-----|-----|-----|-----|
| DSF<br>DSG | 50           | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
|            | 80           | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 100          | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 120          | -   | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| DHG        | 50           | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 | 2.0 |
|            | 80           | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 100          | 1.5 | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
|            | 120          | -   | 1.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |



## 額定輸出扭矩 Nominal Output Torque

減速機輸入轉速 2,000 r/min 時，可以長時間加載的扭矩。

The indicates permissible continuous load torque when the input speed is 2,000 r/min.

## 起動轉矩 Starting Torque

由輸入側使其旋轉時，輸入側開始旋轉的力矩。（平均值，無負荷，環境溫度：25℃）

Input torque needed for input side to start rotating (average value, no load, ambient temperature : 25℃)

## 瞬間容許最大轉矩 Permissible Maximum Momentary Torque

除了負載轉矩、啟動或停止時負載轉矩外，也會有來自外部無法預期的衝擊轉矩。但衝擊轉矩最大值不得超過瞬間容許最大轉矩。

Unexpected impact torque may be applied from the exterior except regular-load torque and load torque for start and stop. The maximum impact torque shall not exceed the permissible maximum momentary torque.


## 起動、停止時的容許峰值轉矩

### Permissible Peak Torque for Start and Stop

起動、停止時，將因負載慣性力矩導致諧波減速機承受較恆定轉矩更大的負載。額定表中的數值，為此時的峰值轉矩容許值。

Load larger than the steady torque is applied to ROBONICDRIVE by the load inertia moment for start and stop. Values from the ratings show the acceptable value at peak torque.

負載轉矩模式範例 Example of Load Torque Pattern



## 無負載運轉力矩 No-load Running Torque

在無負荷條件下轉速 2,000 r/min，使其旋轉所需必要的輸入側力矩。(平均值，無負荷，環境溫度：25°C)  
Input torque needed to keep it running with no load speed 2,000 r/min (average value, no load, ambient temperature :25°C)

## 增速起動轉矩 Output Starting Torque

由輸出側使其旋轉時，輸入側開始旋轉的力矩。(平均值，無負荷，環境溫度：25°C)  
Output torque needed for input side to start rotating (average value, no load, ambient temperature : 25°C)

## 最大輸出扭矩 Max. Output Torque

起動、停止時的最大容許值  
The maximum torque when starting and stopping.

## 額定輸入轉速 Nominal Input Speed

運轉時，輸入轉速的容許值  
The indicates permissible continuous running input speed.

## 噪音值 Noise Level

2,000 r/min 距離 1m 無負載量測  
Noise level is measured in 2,000 r/min, without loading and in distance from the reducer.

## 效率 Efficiency

減速機效率會因以下條件有所差異


The efficiency varies depending on the following conditions.

- 減速比 Reducer Ratio
- 輸入轉速 Input Speed
- 負載轉矩 Load Torque
- 溫度 Temperature
- 潤滑條件 Lubrication Condition


樣本上的數值是輸入轉速 2,000 rpm 額定扭矩負載所測得平均值。

The efficiency in our catalog is average value tested at rated torque loading in input speed 2,000 r/min.


DSF / DSG 14-A□-50




DSF / DSG 14-A□-80




DSF / DSG 14-A□-100



DSF / DSG 14-A□-120





# DSF DSG

諧波減速機

## 機種型號表示 Indication of Model Numbers

| DSF           | 14                                     | — | P                                                                                                              | — | C                                                                                                                           | — | 100                                                                                                       | — | MOTOR              |
|---------------|----------------------------------------|---|----------------------------------------------------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------|---|-----------------------------------------------------------------------------------------------------------|---|--------------------|
| 減速機機型<br>Type | 型號<br>Model                            |   | 樣式<br>Style                                                                                                    |   | 入力樣式<br>Input Style                                                                                                         |   | 速比<br>Ratio                                                                                               |   | 馬達型號<br>Motor Type |
| DSF<br>DSG    | 14<br>17<br>20<br>25<br>32<br>40<br>45 |   | P: 組件式<br>Component Type<br>A: 組合式<br>Unit Type<br>MC: 法蘭式<br>Motor Flange Type<br>S: 入力軸式<br>Input Shaft Type |   | C: 入力迫緊<br>Input Collet<br>K: 入力鍵槽<br>Input Keyway<br><br>樣式 P、A 可以選擇<br>入力樣式<br>Input style is optional<br>for style P, A. |   | 1/50<br>1/80<br>1/100<br>1/120<br>1/160(僅40#)<br><br>型號 Model<br>14#<br>速比 Ratio<br>1/50<br>1/80<br>1/100 |   |                    |

DSF ☐ -PC- ☐  
DSG

### PC

- 組件式 - 入力迫緊  
Component Type - Input Collet



DSF ☐ -AC- ☐  
DSG

### AC


- 組合式 - 入力迫緊  
Unit Type - Input Collet



DSF ☐ -MC- ☐  
DSG

### MC

- 法蘭式 Motor Flange Type



DSF ☐ -PK- ☐  
DSG

### PK

- 組件式 - 入力鍵槽  
Component Type - Input Keyway



DSF ☐ -AK- ☐  
DSG

### AK

- 組合式 - 入力鍵槽  
Unit Type - Input Keyway



DSF ☐ -S- ☐  
DSG

### S


- 入力軸式 Input Shaft Type



## DSF / DSG 產品特性 Characteristic of DSF / DSG


| 規格 Model No.                                              | 單位 Unit                | 減速比 Ratio | 14                                                                     | 17    | 20    | 25    | 32    | 40    | 45    |
|-----------------------------------------------------------|------------------------|-----------|------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|
| 額定輸出扭矩<br>Nominal Output Torque                           | Nm                     | 50        | 7                                                                      | 20    | 30    | 45    | 90    | 140   | 180   |
|                                                           |                        | 80        | 9                                                                      | 27    | 40    | 72    | 138   | 209   | 317   |
|                                                           |                        | 100       | 9                                                                      | 29    | 47    | 77    | 160   | 261   | 385   |
|                                                           |                        | 120       | -                                                                      | 29    | 47    | 77    | 160   | 298   | 408   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 298   | -     |
| 平均負載最大轉矩<br>Max. Output Torque                            | Nm                     | 50        | 9                                                                      | 32    | 40    | 64    | 127   | 200   | 270   |
|                                                           |                        | 80        | 13                                                                     | 33    | 55    | 99    | 195   | 288   | 395   |
|                                                           |                        | 100       | 13                                                                     | 48    | 58    | 123   | 253   | 377   | 507   |
|                                                           |                        | 120       | -                                                                      | 48    | 58    | 123   | 253   | 457   | 629   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 457   | -     |
| 起動停止峰值轉矩<br>Permissible Peak Torque<br>for Start and Stop | Nm                     | 50        | 21                                                                     | 42    | 66    | 112   | 225   | 350   | 450   |
|                                                           |                        | 80        | 27                                                                     | 53    | 86    | 157   | 316   | 452   | 633   |
|                                                           |                        | 100       | 32                                                                     | 67    | 96    | 180   | 346   | 494   | 677   |
|                                                           |                        | 120       | -                                                                      | 67    | 102   | 191   | 367   | 537   | 738   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 566   | -     |
| 瞬間容許最大轉矩<br>Permissible Maximum<br>Momentary Torque       | Nm                     | 50        | 41                                                                     | 81    | 113   | 214   | 440   | 789   | 1093  |
|                                                           |                        | 80        | 53                                                                     | 98    | 146   | 294   | 653   | 1125  | 1461  |
|                                                           |                        | 100       | 56                                                                     | 109   | 169   | 327   | 744   | 1240  | 1806  |
|                                                           |                        | 120       | -                                                                      | 98    | 169   | 350   | 764   | 1345  | 2024  |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 1345  | -     |
| 起動轉矩<br>Starting Torque                                   | cNm                    | 50        | 4                                                                      | 6     | 8     | 15    | 32    | 55    | 77    |
|                                                           |                        | 80        | 3                                                                      | 4     | 5     | 9     | 20    | 35    | 49    |
|                                                           |                        | 100       | 2.5                                                                    | 3.5   | 4     | 8     | 18    | 32    | 43    |
|                                                           |                        | 120       | -                                                                      | 3     | 4     | 7     | 15    | 28    | 39    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 24    | -     |
| 增速起動轉矩<br>Output Starting Torque                          | Nm                     | 50        | 1.5                                                                    | 2.6   | 4.1   | 8.2   | 17    | 29    | 43    |
|                                                           |                        | 80        | 1.6                                                                    | 2.7   | 4.2   | 8.4   | 18    | 30    | 44    |
|                                                           |                        | 100       | 1.7                                                                    | 2.8   | 4.3   | 8.6   | 19    | 32    | 46    |
|                                                           |                        | 120       | -                                                                      | 2.9   | 4.5   | 8.8   | 20    | 34    | 48    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 40    | -     |
| 無負載運轉力矩<br>No-load Running Torque                         | cNm                    | 50        | 4                                                                      | 5     | 7     | 12    | 28    | 48    | 65    |
|                                                           |                        | 80        | 3                                                                      | 4     | 6     | 10    | 20    | 30    | 42    |
|                                                           |                        | 100       | 2                                                                      | 3     | 5     | 8     | 18    | 26    | 38    |
|                                                           |                        | 120       | -                                                                      | 3     | 4     | 7     | 14    | 25    | 35    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 22    | -     |
| 額定輸入轉速<br>Nominal Input Speed                             | rpm                    | 50~160    | 2,000                                                                  | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 |
| 最大輸入轉速<br>Max. Input Speed                                | rpm                    | 50~160    | 6,000                                                                  | 6,000 | 5,000 | 5,000 | 5,000 | 4,000 | 4,000 |
| 慣性力矩 Reducer Inertia                                      | lx10-4kgm <sup>2</sup> | 50~160    | 0.04                                                                   | 0.08  | 0.2   | 0.4   | 1.7   | 4.5   | 8.8   |
| 效率 Efficiency                                             | %                      | 50        | 70                                                                     | 73    | 73    | 73    | 75    | 75    | 75    |
|                                                           |                        | 80        | 68                                                                     | 70    | 72    | 72    | 74    | 74    | 74    |
|                                                           |                        | 100       | 64                                                                     | 66    | 70    | 70    | 72    | 72    | 72    |
|                                                           |                        | 120       | -                                                                      | 64    | 68    | 68    | 70    | 70    | 70    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 65    | -     |
| 使用溫度<br>Operating Temperature                             | °C                     | 50~160    | 環境 Environment -10°C ~ +70°C /<br>最大工作溫度 Max. Working Temperature 90°C |       |       |       |       |       |       |
| 潤滑 Lubrication                                            |                        | 50~160    | 潤滑油脂 Synthetic Grease                                                  |       |       |       |       |       |       |
| 噪音值 Noise Level                                           | dB                     | 50~160    | 52                                                                     | 54    | 56    | 58    | 60    | 62    | 64    |

## MODEL : DSF-PC、DSG-PC




| Code \ Model | 14      | 17      | 20                 | 25      | 32        | 40      | 45                 |
|--------------|---------|---------|--------------------|---------|-----------|---------|--------------------|
| A1           | 8       | 8       | 8、11、14            | 14      | 14、19     | 19      | 19、24              |
| A2           | 3       | 3       | 3、4、5              | 5       | 5、6       | 6       | 6、8                |
| A3           | 9.4     | 9.4     | 9.4、12.7、16.3      | 16.3    | 16.3、21.8 | 21.8    | 21.8、27.3          |
| A4           | M4xP0.7 | M4xP0.7 | M4xP0.7<br>M5xP0.8 | M5xP0.8 | M5xP0.8   | M5xP0.8 | M5xP0.8<br>M6xP1.0 |
| A5           | 23.5    | 23.5    | 23.5、26、31         | 31      | 34、38     | 38      | 38、48              |
| A6           | 22      | 23      | 25.5、27.5          | 30      | 32.5      | 36.5    | 40.5               |
| B1           | 36      | 39      | 42.5、44.5          | 49.5    | 58        | 67.5    | 72                 |
| B2           | 18.5    | 19      | 21、23              | 25.5    | 30        | 33.5    | 34                 |
| B3           | 17.5    | 20      | 21.5               | 24      | 28        | 34      | 38                 |
| B4           | 12.5    | 12.5    | 13.5、15.5          | 15.5    | 16        | 16.5    | 15                 |
| B5           | 6       | 6.5     | 7.5                | 10      | 14        | 17      | 19                 |
| B6           | 2       | 2.5     | 3                  | 3       | 3         | 4       | 4                  |
| B7           | 16.5    | 19      | 20.5               | 23      | 27        | 33      | 36.5               |
| B8           | 2.4     | 3       | 3                  | 3       | 3.2       | 4       | 3.7                |
| C1           | 50      | 60      | 70                 | 85      | 110       | 135     | 155                |
| C2           | 38      | 48      | 54                 | 68      | 90        | 110     | 124                |
| C3           | 23      | 26      | 31                 | 38      | 50        | 64      | 73                 |
| C4           | 11      | 10      | 14                 | 20      | 26        | 32      | 32                 |
| D1           | 6       | 6       | 8                  | 8       | 8         | 8       | 8                  |
| D2           | 4.1     | 5.1     | 5.1                | 6.1     | 8.1       | 10.1    | 12.1               |
| D3           | 17      | 19      | 24                 | 30      | 40        | 50      | 54                 |
| D4           | DSG     | 8       | 16                 | 16      | 16        | 16      | 16                 |
|              | DSF     | 6       | 12                 | 12      | 12        | 12      | 12                 |
| D5           | 3.5     | 3.4     | 3.5                | 4.5     | 5.5       | 6.6     | 8.5                |
| D6           | 44      | 54      | 62                 | 75      | 100       | 120     | 140                |
| D7           | -       | -       | 3.5                | 4.5     | 5.5       | 6.6     | 9                  |
| D8           | M3xP0.5 | M3xP0.5 | M3xP0.5            | M4xP0.7 | M5xP0.8   | M6xP1.0 | M8xP1.25           |
| E1           | 37      | 46      | 53                 | 67      | 86        | 105     | 119                |
| E2           | 1.5     | 1.5     | 2                  | 2       | 2         | 3       | 3                  |
| Weight (g)   | 132     | 195     | 300                | 495     | 1,018     | 3,383   |                    |

# MODEL : DSF-PK、DSG-PK




| Code \ Model | 14        | 17        | 20       | 25      | 32        | 40        | 45        |
|--------------|-----------|-----------|----------|---------|-----------|-----------|-----------|
| A1           | 6、8       | 8         | 8、14     | 14      | 14、19     | 19、24     | 19、24     |
| A2           | 2、3       | 3         | 3、5      | 5       | 5、6       | 6、8       | 6、8       |
| A3           | 7、9.4     | 9.4       | 9.4、16.3 | 16.3    | 16.3、21.8 | 21.8、27.3 | 21.8、27.3 |
| A4           | 2-M4xP0.7 | 2-M4xP0.7 | M4xP0.7  | M5xP0.8 | M5xP0.8   | M5xP0.8   | M6xP1.0   |
| A5           | 18        | 22        | 25       | 32      | 36        | 50        | 50        |
| A6           | 10        | 12.5      | 13.5     | 14.5    | 16        | 20        | 20        |
| A7           | 10.5      | 13        | 14       | 16.3    | 17.45     | 22        | 23        |
| A8           | 14        | 16        | 21       | 24      | 30        | 36        | 36        |
| A9           | 2.3       | 4.2       | 4.3      | 6       | 5         | 7         | 5         |
| B1           | 23.5      | 26.5      | 29       | 34      | 42        | 51        | 57        |
| B2           | 6         | 6.5       | 7.5      | 10      | 14        | 17        | 19        |
| B3           | 17.5      | 20        | 21.5     | 24      | 28        | 34        | 38        |
| B4           | 2         | 2.5       | 3        | 3       | 3         | 4         | 4         |
| B5           | 16.5      | 19        | 20.5     | 23      | 27        | 33        | 36.5      |
| B6           | 2.4       | 3         | 3        | 3       | 3.2       | 4         | 3.7       |
| C1           | 50        | 60        | 70       | 85      | 110       | 135       | 155       |
| C2           | 38        | 48        | 54       | 68      | 90        | 110       | 124       |
| C3           | 23        | 26        | 31       | 38      | 50        | 64        | 73        |
| C4           | 11        | 10        | 14       | 20      | 26        | 32        | 32        |
| D1           | 6         | 6         | 8        | 8       | 8         | 8         | 8         |
| D2           | 4.1       | 5.1       | 5.1      | 6.1     | 8.1       | 10.1      | 12.1      |
| D3           | 17        | 19        | 24       | 30      | 40        | 50        | 54        |
| D4           | DSG       | 8         | 16       | 16      | 16        | 16        | 16        |
|              | DSF       | 6         | 12       | 12      | 12        | 12        | 12        |
| D5           | 3.5       | 3.4       | 3.5      | 4.5     | 5.5       | 6.6       | 8.5       |
| D6           | 44        | 54        | 62       | 75      | 100       | 120       | 140       |
| D7           | -         | -         | 3.5      | 4.5     | 5.5       | 6.6       | 9         |
| D8           | M3xP0.5   | M3xP0.5   | M3xP0.5  | M4xP0.7 | M5xP0.8   | M6xP1.0   | M8xP1.25  |
| E1           | 37        | 46        | 53       | 67      | 86        | 105       | 119       |
| E2           | 1.5       | 1.5       | 2        | 2       | 2         | 3         | 3         |
| Weight (g)   | 100       | 167       | 246      | 446     | 938       | 3,297     |           |

## MODEL : DSF-AC、DSG-AC




| Code \ Model  | 14                  | 17                  | 20                 | 25                 | 32                 | 40                   | 45                  |
|---------------|---------------------|---------------------|--------------------|--------------------|--------------------|----------------------|---------------------|
| A1            | 8                   | 8                   | 8、11、14            | 14                 | 14、19              | 16、19                | 19、24               |
| A2            | 3                   | 3                   | 3、4、5              | 5                  | 5、6                | 6                    | 6、8                 |
| A3            | 9.4                 | 9.4                 | 9.4、12.7、16.3      | 16.3               | 16.3、21.8          | 21.8                 | 21.8、27.3           |
| A4            | M4xP0.7             | M4xP0.7             | M4xP0.7<br>M5xP0.8 | M5xP0.8            | M5xP0.8            | M5xP0.8              | M5xP0.8<br>M6xP1.0  |
| A5            | 23.5                | 23.5                | 23.5、26.5、31       | 31                 | 34、38              | 38                   | 38、48               |
| A6            | 23.5                | 24.5                | 27、29              | 33                 | 38.5               | 46                   | 50、54.5             |
| B1            | 48.5                | 51.5                | 54.5、56.5          | 64.5               | 76                 | 87                   | 93                  |
| B2            | 12.5                | 12.5                | 13.5、15.5          | 15.5               | 16                 | 16.5                 | 15                  |
| B3            | 36                  | 39                  | 41                 | 49                 | 60                 | 70.5                 | 78                  |
| B4            | 34                  | 37                  | 38                 | 46                 | 57                 | 66.5                 | 74                  |
| B5            | 7                   | 8                   | 10                 | 10                 | 12                 | 16                   | 16                  |
| B6            | 4                   | 5                   | 6                  | 6                  | 5                  | 5                    | 6                   |
| C1            | 73                  | 79                  | 93                 | 107                | 138                | 160                  | 180                 |
| C2            | 38                  | 48                  | 56                 | 67                 | 90                 | 110                  | 124                 |
| C3            | 56                  | 63                  | 72                 | 86                 | 113                | 127                  | 148                 |
| C4            | 31                  | 38                  | 45                 | 58                 | 78                 | 90                   | 109.6               |
| C5            | 11                  | 10                  | 14                 | 20                 | 26                 | 32                   | 32                  |
| C6            | 9.4                 | 9.5                 | 9                  | 12                 | 15.2               | 5                    | 18.5                |
| D1            | 6                   | 6                   | 8                  | 8                  | 8                  | 8                    | 8                   |
| D2            | M4xP0.7<br>deep12.5 | M5xP0.8<br>deep12.5 | M6xP1.0<br>deep12  | M8xP1.25<br>deep15 | M10xP1.5<br>deep18 | M10xP1.5<br>deep19.5 | M12xP1.75<br>deep21 |
| D3            | 23                  | 27                  | 32                 | 42                 | 55                 | 68                   | 82                  |
| D4            | DSG                 | 8                   | 8                  | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                  | 8                  | 12                 | 8                    | 12                  |
| D5            | 4.5                 | 4.5                 | 5.5                | 5.5                | 6.5                | 9                    | 9                   |
| D6            | 65                  | 71                  | 82                 | 96                 | 125                | 144                  | 164                 |
| D7            | DSG                 | 8                   | 8                  | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                  | 8                  | 12                 | 8                    | 12                  |
| D8            | M4xP0.7             | M4xP0.7             | M5xP0.8            | M5xP0.8            | M6xP1.0            | M8xP1.25             | M8xP1.25            |
| D9            | 65                  | 71                  | 82                 | 96                 | 125                | 144                  | 164                 |
| O-Ring        | d49.5x2t            | d55.5x2t            | d66.5x2t           | d79.5x2.0t         | d104.5x2t          | d124.5x2t            | d133x2.62t          |
| Output O-Ring | d29x0.6t            | d35x0.6t            | d43x1.5t           | d55x1.5t           | d72x1.5t           | d85x1.5t             | d99.5x2t            |
| Weight (g)    | 555                 | 733                 | 1,039              | 1,629              | 3,463              | 5,174                |                     |

# MODEL : DSF-AK、DSG-AK




| Code \ Model  | 14                  | 17                  | 20                | 25                 | 32                 | 40                   | 45                  |
|---------------|---------------------|---------------------|-------------------|--------------------|--------------------|----------------------|---------------------|
| A1            | 6、8                 | 8                   | 8、14              | 14                 | 14、19              | 19、24                | 19、24               |
| A2            | 2、3                 | 3                   | 3、5               | 5                  | 5、6                | 6、8                  | 6、8                 |
| A3            | 7、9.4               | 9.4                 | 9.4、16.3          | 16.3               | 16.3、21.8          | 21.8、27.3            | 21.8、27.3           |
| A4            | 2-M4xP0.7           | 2-M4xP0.7           | M4xP0.7           | M5xP0.8            | M5xP0.8            | M5xP0.8              | M6xP1.0             |
| A5            | 18                  | 22                  | 25                | 32                 | 36                 | 50                   | 50                  |
| A6            | 10                  | 12.5                | 13.5              | 14.5               | 16                 | 20                   | 20                  |
| A7            | 10.5                | 13                  | 14                | 16.3               | 17.45              | 22                   | 23                  |
| A8            | 14                  | 16                  | 21                | 24                 | 30                 | 36                   | 36                  |
| A9            | 2.3                 | 4.2                 | 4.3               | 6                  | 5                  | 7                    | 5                   |
| B1            | 36                  | 39                  | 41                | 49                 | 60                 | 70.5                 | 78                  |
| B2            | 34                  | 37                  | 38                | 46                 | 57                 | 66.5                 | 74                  |
| B3            | 7                   | 8                   | 10                | 10                 | 12                 | 16                   | 16                  |
| B4            | 4                   | 5                   | 6                 | 6                  | 5                  | 5                    | 6                   |
| C1            | 73                  | 79                  | 93                | 107                | 138                | 160                  | 180                 |
| C2            | 38                  | 48                  | 56                | 67                 | 90                 | 110                  | 124                 |
| C3            | 56                  | 63                  | 72                | 86                 | 113                | 127                  | 148                 |
| C4            | 31                  | 38                  | 45                | 58                 | 78                 | 90                   | 109.6               |
| C5            | 11                  | 10                  | 14                | 20                 | 26                 | 32                   | 32                  |
| C6            | 9.4                 | 9.5                 | 9                 | 12                 | 15.2               | 5                    | 18.5                |
| D1            | 6                   | 6                   | 8                 | 8                  | 8                  | 8                    | 8                   |
| D2            | M4xP0.7<br>deep12.5 | M5xP0.8<br>deep12.5 | M6xP1.0<br>deep12 | M8xP1.25<br>deep15 | M10xP1.5<br>deep18 | M10xP1.5<br>deep19.5 | M12xP1.75<br>deep21 |
| D3            | 23                  | 27                  | 32                | 42                 | 55                 | 68                   | 82                  |
| D4            | DSG                 | 8                   | 8                 | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                 | 8                  | 12                 | 8                    | 12                  |
| D5            | 4.5                 | 4.5                 | 5.5               | 5.5                | 6.5                | 9                    | 9                   |
| D6            | 65                  | 71                  | 82                | 96                 | 125                | 144                  | 164                 |
| D7            | DSG                 | 8                   | 8                 | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                 | 8                  | 12                 | 8                    | 12                  |
| D8            | M4xP0.7             | M4xP0.7             | M5xP0.8           | M5xP0.8            | M6xP1.0            | M8xP1.25             | M8xP1.25            |
| D9            | 65                  | 71                  | 82                | 96                 | 125                | 144                  | 164                 |
| O-Ring        | d49.5x2t            | d55.5x2t            | d66.5x2t          | d79.5x2.0t         | d104.5x2t          | d124.5x2t            | d133x2.62t          |
| Output O-Ring | d29x0.6t            | d35x0.6t            | d43x1.5t          | d55x1.5t           | d72x1.5t           | d85x1.5t             | d99.5x2t            |
| Weight (g)    | 523                 | 705                 | 985               | 1,581              | 3,383              | 5,084                |                     |

## MODEL : DSF-MC、DSG-MC



| Code \ Model  | 14                  | 17                  | 20                 | 25                 | 32                            | 40                   | 45                  |
|---------------|---------------------|---------------------|--------------------|--------------------|-------------------------------|----------------------|---------------------|
| A1            | 8                   | 8                   | 8、11、14            | 14                 | 14、19                         | 16、19                | 19、24               |
| A2            | 3                   | 3                   | 3、4、5              | 5                  | 5、6                           | 5、6                  | 6、8                 |
| A3            | 9.4                 | 9.4                 | 9.4、12.7、16.3      | 16.3               | 16.3、21.8                     | 18.3、21.8            | 21.8、27.3           |
| A4            | M4xP0.7             | M4xP0.7             | M4xP0.7<br>M5xP0.8 | M5xP0.8            | M5xP0.8                       | M5xP0.8              | M5xP0.8<br>M6xP1.0  |
| A5            | 4                   | 4                   | 4、5                | 5                  | 5                             | 5                    | 7                   |
| A6            | 27.5                | 28.5                | 31、34              | 38                 | 43.5                          | 51                   | 57、61.5             |
| A7            | M3xP0.5<br>M4xP0.7  | M3xP0.5<br>M4xP0.7  | M4xP0.7<br>M5xP0.8 | M5xP0.8            | M4xP0.7<br>M5xP0.8<br>M6xP1.0 | M5xP0.8<br>M6xP1.0   | M6xP1.0             |
| A8            | 45、46               | 45、46               | 46、63、70           | 70                 | 65、70<br>90、100               | 70、90<br>98.43       | 90、115              |
| B1            | 52.5                | 55.5                | 58.5、61.5          | 69.5               | 81                            | 92                   | 100                 |
| B2            | 25.5                | 26.5                | 30.5、33.5          | 33.5               | 36                            | 41.5                 | 42                  |
| B3            | 27                  | 29                  | 28                 | 36                 | 45                            | 50.5                 | 58                  |
| B4            | 18.5                | 18.5                | 20.5、23.5          | 23.5               | 24                            | 25.5                 | 26                  |
| B5            | 7                   | 8                   | 10                 | 10                 | 12                            | 16                   | 16                  |
| B6            | 4                   | 5                   | 6                  | 6                  | 5                             | 5                    | 6                   |
| C1            | 73                  | 79                  | 93                 | 107                | 138                           | 160                  | 180                 |
| C2            | 30                  | 30                  | 30、40、50           | 50                 | 36、50<br>70、80                | 50、70、73             | 70、95               |
| C3            | 56                  | 63                  | 72                 | 86                 | 113                           | 127                  | 148                 |
| C4            | 31                  | 38                  | 45                 | 58                 | 78                            | 90                   | 109.6               |
| C5            | 11                  | 10                  | 14                 | 20                 | 26                            | 32                   | 32                  |
| C6            | 9.4                 | 9.5                 | 9                  | 12                 | 15.2                          | 5                    | 18.5                |
| D1            | 6                   | 6                   | 8                  | 8                  | 8                             | 8                    | 8                   |
| D2            | M4xP0.7<br>deep12.5 | M5xP0.8<br>deep12.5 | M6xP1.0<br>deep12  | M8xP1.25<br>deep15 | M10xP1.5<br>deep18            | M10xP1.5<br>deep19.5 | M12xP1.75<br>deep21 |
| D3            | 23                  | 27                  | 32                 | 42                 | 55                            | 68                   | 82                  |
| D4            | DSG                 | 8                   | 8                  | 10                 | 12                            | 10                   | 12                  |
|               | DSF                 | 6                   | 6                  | 8                  | 12                            | 8                    | 12                  |
| D5            | 4.5                 | 4.5                 | 5.5                | 5.5                | 6.5                           | 9                    | 9                   |
| D6            | 65                  | 71                  | 82                 | 96                 | 125                           | 144                  | 164                 |
| D7            | DSG                 | 8                   | 8                  | 10                 | 12                            | 10                   | 12                  |
|               | DSF                 | 6                   | 6                  | 8                  | 12                            | 8                    | 12                  |
| D8            | M4xP0.7             | M4xP0.7             | M5xP0.8            | M5xP0.8            | M6xP1.0                       | M8xP1.25             | M8xP1.25            |
| D9            | 65                  | 71                  | 82                 | 96                 | 125                           | 144                  | 164                 |
| Output O-Ring | d29x0.6t            | d35x0.6t            | d43x1.5t           | d55x1.5t           | d72x1.5t                      | d85x1.5t             | d99.5x2t            |
| Weight (g)    | 633                 | 836                 | 1,155              | 1,831              | 3,881                         | 5,673                |                     |

# MODEL : DSF-S 、 DSG-S



| Code \ Model  | 14                  | 17                  | 20                | 25                 | 32                 | 40                   | 45                  |
|---------------|---------------------|---------------------|-------------------|--------------------|--------------------|----------------------|---------------------|
| A1            | 8                   | 11                  | 11                | 14                 | 14                 | 19                   | 19                  |
| A2            | 3                   | 4                   | 4                 | 5                  | 5                  | 6                    | 6                   |
| A3            | 9.2                 | 12.5                | 12.5              | 16                 | 16                 | 21.5                 | 21.5                |
| A4            | M3xP0.5             | M4xP0.7             | M4xP0.7           | M5xP0.8            | M5xP0.8            | M6xP1.0              | M6xP1.0             |
| A5            | 7                   | 8                   | 8                 | 10                 | 10                 | 12                   | 12                  |
| A6            | 1                   | 1.5                 | 2.5               | 2.5                | 2.5                | 2.5                  | 2.5                 |
| A7            | 10                  | 12                  | 15                | 20                 | 20                 | 25                   | 25                  |
| A8            | 12                  | 16                  | 20                | 25                 | 25                 | 30                   | 30                  |
| A9            | 1                   | 1                   | 1                 | 1                  | 1                  | 1                    | 1                   |
| B1            | 63.5                | 70.5                | 78                | 94                 | 113.5              | 129.5                | 140                 |
| B2            | 36.5                | 41.5                | 50                | 58                 | 68.5               | 79                   | 82                  |
| B3            | 27                  | 29                  | 28                | 36                 | 45                 | 50.5                 | 58                  |
| B4            | 29.5                | 33.5                | 40                | 48                 | 56.5               | 63                   | 66                  |
| B5            | 7                   | 8                   | 10                | 10                 | 12                 | 16                   | 16                  |
| B6            | 4                   | 5                   | 6                 | 6                  | 5                  | 5                    | 5                   |
| C1            | 73                  | 79                  | 93                | 107                | 138                | 160                  | 180                 |
| C2            | 56                  | 63                  | 72                | 86                 | 113                | 127                  | 148                 |
| C3            | 31                  | 38                  | 45                | 58                 | 78                 | 90                   | 109.6               |
| C4            | 11                  | 10                  | 14                | 20                 | 26                 | 32                   | 32                  |
| C5            | 9.4                 | 9.5                 | 9                 | 12                 | 15.2               | 5                    | 18.5                |
| D1            | 6                   | 6                   | 8                 | 8                  | 8                  | 8                    | 8                   |
| D2            | M4xP0.7<br>deep12.5 | M5xP0.8<br>deep12.5 | M6xP1.0<br>deep12 | M8xP1.25<br>deep15 | M10xP1.5<br>deep18 | M10xP1.5<br>deep19.5 | M12xP1.75<br>deep21 |
| D3            | 23                  | 27                  | 32                | 42                 | 55                 | 68                   | 82                  |
| D4            | DSG                 | 8                   | 8                 | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                 | 8                  | 12                 | 8                    | 12                  |
| D5            | 4.5                 | 4.5                 | 5.5               | 5.5                | 6.5                | 9                    | 9                   |
| D6            | 65                  | 71                  | 82                | 96                 | 125                | 144                  | 164                 |
| D7            | DSG                 | 8                   | 8                 | 10                 | 12                 | 10                   | 12                  |
|               | DSF                 | 6                   | 6                 | 8                  | 12                 | 8                    | 12                  |
| D8            | M4xP0.7             | M4xP0.7             | M5xP0.8           | M5xP0.8            | M6xP1.0            | M8xP1.25             | M8xP1.25            |
| D9            | 65                  | 71                  | 82                | 96                 | 125                | 144                  | 164                 |
| Output O-Ring | d29x0.6t            | d35x0.6t            | d43x1.5t          | d55x1.5t           | d72x1.5t           | d85x1.5t             | d99.5x2t            |
| Weight (g)    | 620                 | 818                 | 1,125             | 1,842              | 3,972              | 5,882                |                     |

# MEMO

This image shows a single sheet of white paper with horizontal blue ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.



# DHG

諧波減速機

## 機種型號表示 Indication of Model Numbers

| DHG           | 17                                     | A                                                                                    | C                                                                                                                                                 | 100                                                                                                       | L                                                                                                                 | MOTOR              |
|---------------|----------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|--------------------|
| 減速機機型<br>Type | 型號<br>Model                            | 樣式<br>Style                                                                          | 入力樣式<br>Input Style                                                                                                                               | 速比<br>Ratio                                                                                               | 軸向<br>Shaft Direction                                                                                             | 馬達型號<br>Motor Type |
| DHG           | 14<br>17<br>20<br>25<br>32<br>40<br>45 | A: 組合式<br>Unit Type<br>O: 入力中空軸<br>Hollow Input Shaft<br>S: 入力軸式<br>Input Shaft Type | C: 入力迫緊<br>Input Collet<br>K: 入力鍵槽<br>Input Keyway<br>O: 入力中空軸<br>Hollow Input Shaft<br><br>入力形式 A 可以選擇樣式<br>Input style is optional for style A. | 1/50<br>1/80<br>1/100<br>1/120<br>1/160(僅40#)<br><br>型號 Model<br>14#<br>速比 Ratio<br>1/50<br>1/80<br>1/100 | L: 左軸<br>Left Shaft<br>R: 右軸<br>Right Shaft<br><br>出力形式 O 可以選擇軸向<br>Shaft direction is optional for style type O. |                    |

### DHG □ -AC- □

#### AC

- 組合式 - 入力迫緊  
Unit Type - Input Collet



### DHG □ -O- □

#### O

- 入力中空軸 Hollow Input Shaft



### DHG □ -AK- □

#### AK

- 組合式 - 入力鍵槽  
Unit Type - Input Keyway



### DHG □ -S- □

#### S

- 入力軸式 Input Shaft Type



### DHG □ -AO- □

#### AO


- 組合式 - 入力中空軸  
Unit Type - Hollow Input Shaft



## DHG 產品特性 Characteristic of DHG


| 規格 Model No.                                              | 單位 Unit                | 減速比 Ratio | 14                                                                     | 17    | 20    | 25    | 32    | 40    | 45    |
|-----------------------------------------------------------|------------------------|-----------|------------------------------------------------------------------------|-------|-------|-------|-------|-------|-------|
| 額定輸出扭矩<br>Nominal Output Torque                           | Nm                     | 50        | 7                                                                      | 20    | 30    | 45    | 90    | 140   | 180   |
|                                                           |                        | 80        | 9                                                                      | 27    | 40    | 72    | 138   | 209   | 317   |
|                                                           |                        | 100       | 9                                                                      | 29    | 47    | 77    | 160   | 261   | 358   |
|                                                           |                        | 120       | -                                                                      | 29    | 47    | 77    | 160   | 298   | 408   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 298   | -     |
| 平均負載最大轉矩<br>Max. Output Torque                            | Nm                     | 50        | 9                                                                      | 32    | 40    | 64    | 127   | 200   | 270   |
|                                                           |                        | 80        | 13                                                                     | 33    | 55    | 99    | 195   | 288   | 395   |
|                                                           |                        | 100       | 13                                                                     | 48    | 58    | 123   | 253   | 377   | 507   |
|                                                           |                        | 120       | -                                                                      | 48    | 58    | 123   | 253   | 457   | 629   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 457   | -     |
| 起動停止峰值轉矩<br>Permissible Peak Torque<br>for Start and Stop | Nm                     | 50        | 21                                                                     | 42    | 66    | 112   | 225   | 350   | 450   |
|                                                           |                        | 80        | 27                                                                     | 53    | 86    | 157   | 316   | 452   | 633   |
|                                                           |                        | 100       | 32                                                                     | 67    | 96    | 180   | 346   | 494   | 677   |
|                                                           |                        | 120       | -                                                                      | 67    | 102   | 191   | 367   | 537   | 738   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 566   | -     |
| 瞬間容許最大轉矩<br>Permissible Maximum<br>Momentary Torque       | Nm                     | 50        | 41                                                                     | 81    | 113   | 214   | 440   | 789   | 1093  |
|                                                           |                        | 80        | 53                                                                     | 98    | 146   | 294   | 653   | 1125  | 1461  |
|                                                           |                        | 100       | 56                                                                     | 109   | 169   | 327   | 744   | 1240  | 1806  |
|                                                           |                        | 120       | -                                                                      | 98    | 169   | 350   | 764   | 1345  | 2024  |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 1345  | -     |
| 起動轉矩<br>Starting Torque                                   | cNm                    | 50        | 11                                                                     | 30    | 40    | 58    | 86    | 140   | 165   |
|                                                           |                        | 80        | 10                                                                     | 28    | 36    | 56    | 80    | 130   | 150   |
|                                                           |                        | 100       | 9                                                                      | 26    | 34    | 52    | 73    | 120   | 140   |
|                                                           |                        | 120       | -                                                                      | 24    | 30    | 48    | 68    | 110   | 125   |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 105   | -     |
| 增速起動轉矩<br>Output Starting Torque                          | Nm                     | 50        | 2.5                                                                    | 3.5   | 4.5   | 8.5   | 18    | 32    | 43    |
|                                                           |                        | 80        | 2.7                                                                    | 3.8   | 5     | 9     | 19    | 35    | 45    |
|                                                           |                        | 100       | 2.8                                                                    | 4.2   | 5.5   | 9.5   | 21    | 37    | 48    |
|                                                           |                        | 120       | -                                                                      | 4.5   | 6     | 10    | 23    | 42    | 55    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 47    | -     |
| 無負載運轉力矩<br>No-load Running Torque                         | cNm                    | 50        | 4                                                                      | 6     | 8     | 15    | 30    | 53    | 70    |
|                                                           |                        | 80        | 3                                                                      | 4     | 5.5   | 10    | 22    | 38    | 50    |
|                                                           |                        | 100       | 2.5                                                                    | 3.5   | 5     | 9     | 20    | 33    | 45    |
|                                                           |                        | 120       | -                                                                      | 3.2   | 4.5   | 8     | 16    | 30    | 40    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 27    | -     |
| 額定輸入轉速 Nominal Input Speed                                | rpm                    | 50~160    | 2,000                                                                  | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 |
| 最大輸入轉速 Max. Input Speed                                   | rpm                    | 50~160    | 6,000                                                                  | 6,000 | 5,000 | 5,000 | 5,000 | 4,000 | 4,000 |
| 慣性力矩 Reducer Inertia                                      | lx10-4kgm <sup>2</sup> | 50~160    | 0.04                                                                   | 0.08  | 0.2   | 0.4   | 1.7   | 4.5   | 8.8   |
| 效率 Efficiency                                             | %                      | 50        | 70                                                                     | 73    | 73    | 73    | 75    | 75    | 75    |
|                                                           |                        | 80        | 68                                                                     | 70    | 72    | 72    | 74    | 74    | 74    |
|                                                           |                        | 100       | 64                                                                     | 66    | 70    | 70    | 72    | 72    | 72    |
|                                                           |                        | 120       | -                                                                      | 64    | 68    | 68    | 70    | 70    | 70    |
|                                                           |                        | 160       | -                                                                      | -     | -     | -     | -     | 65    | -     |
| 使用溫度 Operating Temperature                                | °C                     | 50~160    | 環境 Environment -10°C ~ +70°C /<br>最大工作溫度 Max. Working Temperature 90°C |       |       |       |       |       |       |
| 潤滑 Lubrication                                            |                        | 50~160    | 潤滑油脂 Synthetic Grease                                                  |       |       |       |       |       |       |
| 噪音值 Noise Level                                           | dB                     | 50~160    | 52                                                                     | 54    | 56    | 58    | 60    | 62    | 64    |

# MODEL : DHG-AC




| Code \ Model | 14         | 17         | 20              | 25         | 32         | 40          | 45           |
|--------------|------------|------------|-----------------|------------|------------|-------------|--------------|
| A1           | 8          | 8          | 8、11、14         | 14         | 14、19      | 19          | 19           |
| A2           | 3          | 3          | 3、4、5           | 5          | 5、6        | 6           | 6            |
| A3           | 9.4        | 9.4        | 9.4、12.7、16.3   | 16.3       | 16.3、21.8  | 21.8        | 21.8         |
| A4           | M4xP0.7    | M4xP0.7    | M4xP0.7、M5xP0.8 | M5xP0.8    | M5xP0.8    | M5xP0.8     | M5xP0.8      |
| A5           | 23.5       | 23.5       | 23.5、26.5、31    | 31         | 34、38      | 38          | 38           |
| A6           | 22         | 23         | 25.5、27.5       | 30         | 32.5       | 36.5        | 38.5         |
| B1           | 36         | 39.5       | 42.5、44.5       | 49.5       | 58         | 67          | 73           |
| B2           | 12.5       | 13         | 13.5、15.5       | 15.5       | 16         | 16          | 16.5         |
| B3           | 7          | 7.5        | 8.5             | 12         | 15         | 18          | 20           |
| B4           | 14.1       | 16         | 17.5            | 18.7       | 23.4       | 29          | 32           |
| B5           | 2.4        | 3          | 3               | 3.3        | 3.6        | 4           | 4.5          |
| B6           | 6          | 6.5        | 7.5             | 10         | 14         | 17          | 19           |
| C1           | 70         | 80         | 90              | 110        | 142        | 170         | 190          |
| C2           | 50         | 60         | 70              | 85         | 110        | 135         | 155          |
| C3           | 70         | 80         | 90              | 110        | 142        | 170         | 190          |
| C4           | 48         | 60         | 70              | 88         | 114        | 140         | 158          |
| D1           | 8          | 12         | 12              | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5             | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84              | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16              | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5             | 4.5        | 5.5        | 6.5         | 8.5          |
| D6           | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L      | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| E1           | 44         | 54         | 62              | 77         | 100        | 122         | 140          |
| E2           | 38         | 46         | 54              | 67         | 86         | 106         | 119          |
| E3           | 1.5        | 1.5        | 2               | 2          | 2          | 2           | 2            |
| E4           | 30         | 36         | 44              | 56         | 72         | 92          | 105          |
| E5           | 2          | 2          | 2               | 2          | 2          | 2.5         | 3            |
| Weight (g)   | 312        | 595        | 811             | 1,328      | 2,707      | 4,628       | 6,732        |

# MODEL : DHG-AK




| Code \ Model | 14         | 17         | 20         | 25         | 32         | 40          | 45           |
|--------------|------------|------------|------------|------------|------------|-------------|--------------|
| A1           | 6、8        | 8          | 8、14       | 14         | 14、19      | 19、24       | 19、24        |
| A2           | 3、3        | 3          | 3、5        | 5          | 5、6        | 6、8         | 6、8          |
| A3           | 7、9.4      | 9.4        | 9.4、16.3   | 16.3       | 16.3、21.8  | 21.8、27.3   | 21.8、27.3    |
| A4           | 2-M4xP0.7  | 2-M4xP0.7  | M4xP0.7    | M5xP0.8    | M5xP0.8    | M5xP0.8     | M6xP1.0      |
| A5           | 18         | 22         | 25         | 32         | 36         | 50          | 50           |
| A6           | 10         | 12.5       | 13.5       | 14.5       | 16         | 20          | 20           |
| A7           | 10.5       | 13         | 14         | 16.3       | 17.45      | 23          | 22           |
| A8           | 14         | 16         | 21         | 24         | 30         | 36          | 36           |
| A9           | 2.3        | 4.2        | 4.3        | 6          | 5          | 7           | 5            |
| B1           | 23.5       | 26.5       | 29         | 34         | 42         | 51          | 56.5         |
| B2           | 7          | 7.5        | 8.5        | 12         | 15         | 18          | 20           |
| B3           | 14.1       | 16         | 17.5       | 18.7       | 23.4       | 29          | 32           |
| B4           | 2.4        | 3          | 3          | 3.3        | 3.6        | 4           | 4.5          |
| B5           | 6          | 6.5        | 7.5        | 10         | 14         | 17          | 19           |
| C1           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C2           | 50         | 60         | 70         | 85         | 110        | 135         | 155          |
| C3           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C4           | 48         | 60         | 70         | 88         | 114        | 140         | 158          |
| D1           | 8          | 12         | 12         | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84         | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16         | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 8.5          |
| D6           | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| E1           | 38         | 46         | 54         | 67         | 86         | 106         | 119          |
| E2           | 1.5        | 1.5        | 2          | 2          | 2          | 2           | 2            |
| E3           | 30         | 36         | 44         | 56         | 72         | 92          | 105          |
| E4           | 2          | 2          | 2          | 2          | 2          | 2.5         | 3            |
| Weight (g)   | 280        | 567        | 757        | 1,280      | 2,628      | 4,536       | 6,642        |

# MODEL : DHG-AO




| Code \ Model | 14         | 17         | 20         | 25         | 32         | 40          | 45           |
|--------------|------------|------------|------------|------------|------------|-------------|--------------|
| A1           | 14         | 19         | 21         | 29         | 36         | 46          | 52           |
| A2           | 20         | 25         | 30         | 38         | 45         | 59          | 64           |
| A3           | -          | -          | -          | 40         | -          | 59          | 65           |
| A4           | 20         | 25         | 30         | 40         | 45         | 60          | 65           |
| A5           | 20         | 25         | 30         | 40         | 50         | 60          | 65           |
| A6           | 24         | 29         | 34         | 43         | 50         | 65          | 70           |
| A7           | 53         | 56.5       | 51.5       | 55.5       | 65.5       | 79          | 85           |
| A8           | 13         | 13         | 13         | 12.5       | 13.5       | 16          | 19           |
| A9           | 20.5       | 24         | 20.5       | 24         | 26         | 35          | 36           |
| A10          | 19.5       | 19.5       | 18         | 19         | 26         | 28          | 30           |
| A11          | 7          | 7          | 7          | 7          | 7          | 10          | 10           |
| A12          | 7          | 7          | 8          | 7          | 12         | 13          | 13           |
| A13          | 18         | 18.5       | 17         | 18         | 22         | 27          | 29           |
| A14          | 17         | 19.5       | 17.5       | 19.5       | 21.5       | 25          | 27           |
| A15          | 18         | 18.5       | 17         | 18         | 22         | 27          | 29           |
| A16          | 3-M3xP0.5  | 3-M3xP0.5  | M3xP0.5    | M3xP0.5    | M3xP0.5    | M4xP0.7     | M4xP0.7      |
| A17          | -          | -          | 6          | 6          | 6          | 8           | 8            |
| A18          | -          | -          | 25.5       | 33.5       | 40.5       | 52          | 58           |
| B1           | 53         | 56.5       | 51.5       | 55.5       | 65.5       | 79          | 85           |
| B2           | 13.5       | 14         | 13         | 11.5       | 11.5       | 15          | 15           |
| B3           | 23.5       | 26.5       | 29         | 34         | 42         | 51          | 56.5         |
| B4           | 16         | 16         | 9.5        | 10         | 12         | 13          | 13.5         |
| B5           | 7          | 7.5        | 8.5        | 12         | 15         | 18          | 20           |
| B6           | 14.1       | 16         | 17.5       | 18.7       | 23.4       | 29          | 32           |
| B7           | 2.4        | 3          | 3          | 3.3        | 3.6        | 4           | 4.5          |
| B8           | 6          | 6.5        | 7.5        | 10         | 14         | 17          | 19           |
| C1           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C2           | 50         | 60         | 70         | 85         | 110        | 135         | 155          |
| C3           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C4           | 48         | 60         | 70         | 88         | 114        | 140         | 158          |
| D1           | 8          | 12         | 12         | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84         | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16         | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 8.5          |
| D6           | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| Weight (g)   | 340        | 630        | 848        | 1,416      | 2,736      | 4,659       | 6,849        |

# MODEL : DHG-O




| Code \ Model | 14         | 17         | 20         | 25         | 32         | 40          | 45           |
|--------------|------------|------------|------------|------------|------------|-------------|--------------|
| A1           | 14         | 19         | 21         | 29         | 36         | 46          | 52           |
| A2           | 20         | 25         | 30         | 38         | 45         | 59          | 64           |
| A3           | 3-M3xP0.5  | 3-M3xP0.5  | M3xP0.5    | M3xP0.5    | M3xP0.5    | M4xP0.7     | M4xP0.7      |
| A4           | -          | -          | 6          | 6          | 6          | 8           | 8            |
| A5           | -          | -          | 25.5       | 33.5       | 40.5       | 52          | 58           |
| B1           | 53         | 56.5       | 51.5       | 55.5       | 65.5       | 79          | 85           |
| B2           | 20.5       | 21.5       | 21.5       | 23.5       | 26.5       | 33          | 35           |
| B3           | 20.5       | 23         | 25         | 26         | 32         | 38          | 42           |
| B4           | -          | -          | 5          | 6          | 7          | 8           | 8            |
| B5           | 8          | 8.5        | 7          | 6          | 5          | 7           | 7            |
| B6           | 11.5       | 12         | 13.5       | 15.5       | 20.5       | 25          | 27           |
| B7           | 8          | 8.5        | 9          | 8.5        | 9.5        | 13          | 12           |
| C1           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C2           | 54         | 64         | 75         | 90         | 115        | 140         | 160          |
| C3           | 36         | 45         | 50         | 60         | 85         | 100         | 120          |
| C4           | 74         | 84         | 95         | 115        | 147        | 175         | 195          |
| D1           | 8          | 12         | 12         | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84         | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16         | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 8.5          |
|              | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| D6           | 44         | 54         | 62         | 77         | 100        | 122         | 140          |
| E1           | 36         | 45         | -          | -          | -          | -           | -            |
| E2           | 6.5        | 6.5        | -          | -          | -          | -           | -            |
| E3           | 5.5        | 5.5        | -          | -          | -          | -           | -            |
| E4           | 2.5        | 2.5        | -          | -          | -          | -           | -            |
| Weight (g)   | 470        | 808        | 1,168      | 1,709      | 3,500      | 5,983       | 8,254        |

# MODEL : DHG-OR




| Code \ Model | 14         | 17         | 20         | 25         | 32         | 40          | 45           |
|--------------|------------|------------|------------|------------|------------|-------------|--------------|
| A1           | 14         | 19         | 21         | 29         | 36         | 46          | 52           |
| A2           | 20         | 25         | 30         | 38         | 45         | 59          | 64           |
| A3           | 3-M3xP0.5  | 3-M3xP0.5  | M3xP0.5    | M3xP0.5    | M3xP0.5    | M4xP0.7     | M4xP0.7      |
| A4           | -          | -          | 6          | 6          | 6          | 8           | 8            |
| A5           | -          | -          | 25.5       | 33.5       | 40.5       | 52          | 58           |
| B1           | 53         | 56.5       | 51.5       | 55.5       | 65.5       | 79          | 85           |
| B2           | 26.5       | 27         | 25.5       | 28.5       | 32.5       | 40          | 42           |
| B3           | 20.5       | 23         | 25         | 26         | 32         | 38          | 42           |
| B4           | -          | -          | 1          | 1          | 1          | 1           | 1            |
| B5           | 14         | 14         | 11         | 11         | 11         | 14          | 14           |
| B6           | 11.5       | 12         | 13.5       | 15.5       | 20.5       | 25          | 27           |
| B7           | 8          | 8.5        | 9          | 8.5        | 9.5        | 13          | 12           |
| B8           | -          | -          | 5          | 6          | 7          | 8           | 8            |
| C1           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C2           | 54         | 64         | 75         | 90         | 115        | 140         | 160          |
| C3           | 36         | 45         | 50         | 60         | 85         | 100         | 120          |
| C4           | 74         | 84         | 95         | 115        | 147        | 175         | 195          |
| D1           | 8          | 12         | 12         | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84         | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16         | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 8.5          |
| D6           | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| E1           | 36         | 45         | -          | -          | -          | -           | -            |
| E2           | 6.5        | 6.5        | -          | -          | -          | -           | -            |
| E3           | 7.5        | 7.5        | -          | -          | -          | -           | -            |
| E4           | 2.5        | 2.5        | -          | -          | -          | -           | -            |
| Weight (g)   |            |            |            |            |            |             |              |

# MODEL : DHG-S



DHG14.DHG17





| Code \ Model | 14         | 17         | 20         | 25         | 32         | 40          | 45           |
|--------------|------------|------------|------------|------------|------------|-------------|--------------|
| A1           | 8          | 8          | 10         | 14         | 14         | 16          | 19           |
| A2           | -          | -          | 3          | 5          | 5          | 5           | 6            |
| A3           | -          | -          | 11.2       | 16         | 16         | 18          | 21.5         |
| A4           | M3xP0.5    | M3xP0.5    | M3xP0.5    | M5xP0.8    | M5xP0.8    | M5xP0.8     | M6xP1.0      |
| A5           | 6          | 6          | 6          | 10         | 10         | 10          | 12           |
| A6           | 14         | 16         | 20         | 25         | 25         | 30          | 30           |
| A7           | -          | -          | 2.5        | 2.5        | 2.5        | 2.5         | 2.5          |
| A8           | -          | -          | 15         | 20         | 20         | 25          | 25           |
| B1           | 50.5       | 56         | 63.5       | 72.5       | 84.5       | 100         | 108          |
| B2           | 15         | 15.5       | 17.5       | 20.5       | 26.5       | 31          | 35           |
| B3           | 20.5       | 23         | 25         | 26         | 32         | 38          | 42           |
| B4           | 15         | 17.5       | 21         | 26         | 26         | 31          | 31           |
| B5           | 2.5        | 3          | 3          | 3          | 5          | 5           | 7            |
| B6           | 11.5       | 11.5       | 13.5       | 15.5       | 20.5       | 25          | 27           |
| B7           | 8          | 8.5        | 9          | 8.5        | 9.5        | 13          | 12           |
| C1           | 70         | 80         | 90         | 110        | 142        | 170         | 190          |
| C2           | 54         | 64         | 75         | 90         | 115        | 140         | 160          |
| C3           | 36         | 45         | 50         | 60         | 85         | 100         | 120          |
| C4           | 74         | 84         | 95         | 115        | 147        | 175         | 195          |
| D1           | 8          | 12         | 12         | 12         | 12         | 12          | 18           |
| D2           | 3.5        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 6.5          |
| D3           | 64         | 74         | 84         | 102        | 132        | 158         | 180          |
| D4           | 8          | 16         | 16         | 16         | 16         | 16          | 12           |
| D5           | 3.3        | 3.5        | 3.5        | 4.5        | 5.5        | 6.5         | 8.5          |
| D6           | M3xP0.5x6L | M3xP0.5x6L | M3xP0.5x6L | M4xP0.7x8L | M5xP0.8x8L | M6xP1.0x10L | M8xP1.25x10L |
| Weight (g)   | 450        | 763        | 1,057      | 1,675      | 3,458      | 5,906       | 8,463        |

## MODEL : DSS-14

RATIO : 100

精密旋轉平台 High Precision Rotary Reducer







### 產品特性 Features

|        |                         |        |
|--------|-------------------------|--------|
| 額定輸出扭矩 | Nominal Output Torque   | : 9Nm  |
| 容許載重   | Permissible Thrust Load | : 100N |
| 容許慣量載重 | Permissible Moment Load | : 10Nm |




# 客製化諧波減速機 Customized ROBONICDRIVE




## 諧波減速機 DSF-MC / DSG-MC 與馬達安裝指南


## ROBONICDRIVE DSF-MC / DSG-MC and Motor Mounting Instructions



核對馬達型號與減速機規格是否正確。並將配合面擦拭乾淨。  
Confirm the motor, and gearbox size. Clean up the mounting surface.




確認減速機與馬達是否有鍵配合。  
Confirm whether the reducer and motor are keyed together.




請使用帶油封之電機，避免潤滑脂洩漏至電機。  
Please use a motor with oil seal to prevent grease leaking to the motor.




取出塞頭，使用六角扳手將迫緊環螺絲鬆開。並將扳手與螺絲對準孔位。  
Remove the plug on the adapter plate. Rotate the set collar till the bolt is line up.




將馬達垂直裝入減速機。  
Put the motor into the gearbox vertically.



依序 1~4 使用扭力扳手鎖上內六角螺絲。  
Tighten the mounting bolt in 1~4 order with torque wrench.



使用扭力扳手將迫緊環螺絲鎖緊。  
Tighten the set collar bolt with torque wrench.



裝回塞頭並鎖緊。  
Tighten back the screw plug.

1. 務必先鎖緊馬達固定面，才能鎖緊馬達軸心迫緊環。  
To be sure to tighten motor first and then to tighten the set collar on motor shaft.
2. 請依步驟順序組裝，尤其步驟 6、7 不可顛倒。  
Please assembly in order according to above steps, especially for step 6 and step 7.
3. 安裝完畢後，請將塞頭回塞，避免細小物品掉入減速機中。  
Please noted that tighten back the screw plug to protect the gear box.